



LUMENSOURCE

SPECIFICATION GRADE LED

Project: _____

Date: _____

Notes: _____

Configuration: _____

CONTEMPORARY

VC SERIES

The Lumensource Posts provides an excellent replacement to traditional light sources such as fluorescent and metal halide. Corrosion resistant, cast A356 aluminum alloy housing and heavy gauge spun aluminum hood provides high performance, energy saving, and long lasting light output perfect for area lighting needs.

FEATURES

- Universal input voltage for easy installation
- Protective powder coating for lasting appearance
- Segmented specular Alzak reflector
- Extruded and/or cast aluminum arms



ORDERING INFORMATION

Standard Configuration:

CON	VC	40	W	277	FG	GS	WM	CA	BK	
model	series	wattage	color	voltage	lens	mid section	mounting	arms	finish	options

Model

CON- Contemporary

Series

VC - 24" A x 13" B

Wattage

40W, 80W, 120W

Color

W - Warm White 3000K
C - Cool white 5000K

Voltage

120, 208, 240, 277,
347*, 480*, (VAC input)

* Consult factory for availability


Lens

FG - Flat Glass
CG - Convex Glass
PD - Polycarbonate Dome
RF - Refractor




Mid Section

GS - Glow Section
SS - Solid Section
IW - Illuminated Windows
IS - Illuminating Slots



Mounting



Arms



Finish

BK - Black
BZ - Bronze
GR - Green
VG - Verde Green
CC - Custom Color

Options

HS - House Shield
FS - Fuse
PC - Photo Cell
SP - Surge Protector

2964 W Valley Blvd., Alhambra, CA., 91803 USA
Tel: 626-570-9333 Fax: 626-570-9777
Inquiries: answers@lumensource.biz
Visit: lumensource.biz

