



# LUMENSOURCE

SPECIFICATION GRADE LED

Project: \_\_\_\_\_

Date: \_\_\_\_\_

Notes: \_\_\_\_\_

Configuration: \_\_\_\_\_

## DECORATIVE

### LO SERIES

The Lumensource Posts provides an excellent replacement to traditional light sources such as fluorescent and metal halide. Corrosion resistant cast A356 aluminum alloy pole fitter provides high performance, energy saving, and long lasting light output perfect for area lighting needs.



## FEATURES

- Universal input voltage for easy installation
- Protective powder coating for lasting appearance
- Spun aluminum hood 1/8" thick with (2) 1" O.D. extruded aluminum supports

## ORDERING INFORMATION

Standard Configuration:



Model	Voltage	Mounting
POS-Post	120	WM-Wall Mount
Series	208	PT-Post
	240	1S-Single
	277	2T-Twin
ACA-31" A x 31.5" B	(VAC input)	
Wattage	Finish	Arm
40W	BL - Black	CU
80W	BZ - Bronze	CKU
120W	GR- Green	CIU
Color	VG - Verde Green	CLU
W - Warm White 3000K	CC- Custom Color	CNU
C - Cool white 5000K		Optics
		LR-Lower Reflector
		GR-Glass Reflector
		DR-Diffused Reflector

2964 W Valley Blvd., Alhambra, CA., 91803 USA  
 Tel: 626-570-9333 Fax: 626-570-9777  
 Inquiries: answers@lumensource.biz  
 Visit: lumensource.biz

