



# LUMENSOURCE

SPECIFICATION GRADE LED

Project: \_\_\_\_\_

Date: \_\_\_\_\_

Notes: \_\_\_\_\_

Configuration: \_\_\_\_\_

## RECESSED

### INDIRECT SERIES

The Lumensource Recessed Indirect In provides an excellent replacement to traditional light sources such as fluorescent. The original sheet metal housing provides high performance, energy saving, and long lasting light output perfect for area lighting needs.




**Side Basket**

## FEATURES

- Universal input voltage or dimmable option available
- Protective powder coating for lasting appearance
- Standard white perforated holes with acrylic overlay
- Sloping sides softly reflect light backwards
- Recessed T-bar lay-in grid ceiling mount



**Center Basket**



Specifications: 2X4

Length: 48 (1218)

Width: 24 (608)

Depth: 5-1/2 (140)

Specifications: 2X2

Length: 24 (608)

Width: 24 (608)

Depth: 5-1/2 (140)

Specifications: 1X4

Length: 48 (1218)

Width: 12 (302)

Depth: 5-1/2 (140)

## ORDERING INFORMATION

Standard Configuration:

All dimensions are in inches (millimeters).



Model	Color	Diffuser	
IR - Indirect Recessed	C - Cool white 5000K	RH (Standard)	RH - Round Holes (Standard)
Series	Voltage AC input	Options	
SB - Side Basket	120	DM - Dimmable (120V only)	PA - Prismatic Acrylic
CB - Center Basket	277		SR - Specular Reflector
Size			LB - Louver Blade
1x4 (60W)			
2x2 (60W)			
2x4 (120W)			



**Center Basket**



**Side Basket**

3052 W Valley Blvd., Alhambra, CA., 91803 USA  
 Tel: 626-570-9333 Fax: 626-570-9777  
 Inquiries: answers@lumensource.biz  
 Visit: lumensource.biz

