



LUMENSOURCE

SPECIFICATION GRADE LED

Project: _____

Date: _____

Notes: _____

Configuration: _____

PARABOLIC

TROFFER SERIES


The Lumensource Parabolic Troffer provides an excellent replacement to traditional light sources such as fluorescent. The original sheet metal housing provides high performance, energy saving, and long lasting light output perfect for area lighting needs.



2 x 4

FEATURES

- Universal input voltage or dimmable option available
- Protective powder coating for lasting appearance
- Low-glare Anodized specular aluminum parabolic
- Surface or recessed mounting options available



Specifications: 2X4

Length: 48 (1218)
Width: 24 (608)
Depth: 5-1/2 (140)

Specifications: 2X2

Length: 24 (608)
Width: 24 (608)
Depth: 5-1/2 (140)

Specifications: 1X4

Length: 48 (1218)
Width: 12 (302)
Depth: 5-1/2 (140)

All dimensions are in inches (millimeters).

ORDERING INFORMATION

Standard Configuration:



Model

PR - Parabolic Troffer

Series

RC - Recessed Mount
SM - Surface Mount

Size

1x4 (60W)
2x2 (60W)
2x4 (120W)

Color

C - Cool white 5000K

Voltage AC input

120
277

Cells

A - Specular Aluminum
W - Coated White

Options

DM - Dimmable (120V only)
VH - Hanging Loop



2 x 2



1 x 4

